

# CERAMIC ENGINE PROTECTOR



## BENEFITS

- ✓ Significantly reduces friction and wear
- ✓ Reduces fuel and oil consumption
- ✓ Restores engine power
- ✓ Provides long term protection of your engine
- ✓ Improves load carrying capacity of the lube film
- ✓ Reduces emission of hazardous exhaust gases

## USAGE

For all gasoline, diesel and LPG engines with or without turbochargers. Can be mixed with all commercially available engine oils. Does not clog filters and is not harmful for catalytic converters. Not suitable for motorcycles using a wet clutch.

## DIRECTION

Shake well before use. Add contents of one bottle to the warm motor oil, preferably shortly after oil change. Drive approximately 15 minutes to obtain optimum result. Make sure the oil contents do not exceed the maximum oil level in your engine.

## DOSAGE

One bottle treats 4 to 6 litres of motor oil. Due to its outstanding bonding to metal, this advanced product retains its properties and effectiveness even after oil change. Recommended use: every 50.000 km.

## TECHNICAL SPECIFICATIONS

Density g/cm <sup>3</sup>	0,90
Flash Point	> 200°C
Viscosity @ 20°C	~ 720 mPa.s
Colour	Cream / White

## PACKAGING DETAILS

Art. No.	68130
Content	250 ml
Packaging	12x250 ml
Pallet	70 cartons
Languages	EN, FR, DE, ES, NL, PT, IT