CVT FLUID

DESCRIPCIÓN DEL PRODUCT

ARDINA ATF CVT Fluid es un fluido CVT totalmente sintético de alto rendimiento para su uso en las últimas cajas de cambios de transmisión variable continua (CVT) que transfieren la tracción a través de cadenas de tracción de acero o correas de empuje. (CVT) que transfieren la tracción a través de cadenas de tracción de acero o correas de empuje. Ha sido formulado con una base 100% sintética combinada con un paquete de aditivos único.

NIVEL DE RENDIMIENTO

- Toyota CVTF TC
- Nissan NS-3
- Mitsubishi CVTF-J1
- Suzuki CVTF Green 1
- Ford WSS-M2C928
- Toyota CVTF FE
- Honda HMMF
- Subaru ECVT
- Hyundai SP-III
- Nissan NS-1
- Honda HCF2
- Subaru iCVT
- EZL 799
- MB 236.20
- Nissan NS-2
- Mitsubishi SP-III
- Daihatsu Ammix CVT
- Chrysler/Jeep NS-2

ESPECIFICACIONES TÉCNICAS

Densidad kg/L @ 15°C	0,847
Viscosidad @ 40°C mm2/s	35,00
Viscosidad @ 100°C mm2/s	7,90
Índice de viscosidad	185
Punto de inflamación COC	210°C
Punto de fluidez	-48°C

DETALLES DEL ENVASE

Art. No.	68381
	68387
Contenido	1L/4L/5L/200L
Paleta	N/A

ARDINA CAR CARE B.V. | Molenwerf 56 | 1911 DB Uitgeest | The Netherlands | sales@ardinacarcare.com

The content of this sheet is correct to the best of our knowledge. We do not accept responsibility for damage as a consequence of incompleteness or negligence and inaccuracies in this in- formation sheet. Recommendations or suggestions made in this sheet are made without guarantee of respresentations as to results. All terms of sale of the supplier are applied here.