

MOTOR OIL SAE 5W20 PRO



PRODUCT DESCRIPTION

ARDINA Motor Oil SAE 5W20 PRO is a modern synthetic engine oil. Based on specially selected synthetic base oils with a high viscosity index. Combined with the specially selected high tech additives this motor oil is suitable for use in petrol engines of passenger cars that prescribe an oil with GM Dexos 1™ Gen 2 specification.

PERFORMANCE LEVEL

- ✓ API SP Resource Conserving
- ✓ ILSAC GF-6A
- ✓ GM Dexos 1™ Gen 2
- ✓ Chrysler MS 6395
- ✓ Ford WSS-M2C945-A/B1 / WSS-M2C960-A1

TECHNICAL SPECIFICATIONS

Density kg/L @ 15°C	0,849
Viscosity @-35°C mPa.s	3940
Viscosity @ 40°C mm2/s	48,00
Viscosity @ 100°C mm2/s	8,80
Viscosity Index	166
Flash Point COC	226°C
Pour Point	-33°C
Total Base Number	8,5 mgKOH/g
Ash, Sulphated	0,89%

PACKAGING DETAILS

Art. No.	68520
	65730
Content	1L/4L/5L/200L
Pallet	N/A



ARDINA CAR CARE B.V. | Molenwerf 56 | 1911 DB Uitgeest | The Netherlands | sales@ardinacarcare.com

The content of this sheet is correct to the best of our knowledge. We do not accept responsibility for damage as a consequence of incompleteness or negligence and inaccuracies in this information sheet. Recommendations or suggestions made in this sheet are made without guarantee of representations as to results. All terms of sale of the supplier are applied here.