

PRODUCT DESCRIPTION

ARDINA Sili Gasket Pro is a low volatile automotive sealant, supplied as a paste like, one component material. Sili Gasket Pro has been specifically formulated to resist slumping and sagging even when applied to vertical and horizontal surfaces overhead.

BENEFITS

- ✓ Formulated for resisting high temperatures (up to 330°C)
- ✓ Ideal for heavy duty applications and areas with low temperatures (-60°C)
- ✓ Can replace almost any cut gasket by making reliable “formed-in-place” gaskets that resist cracking, shrinking and migrating caused by thermal cycling

USAGE

Sili Gasket Pro can be used for sealing turbo housings, exhaust manifolds and oxygen sensors. Fixing automotive and appliance trim including: metal, fabric and fabric backed plastics. For sealing trailers, trucks, cabs, bonding and sealing appliance parts. Not recommended for use on PE, PP, PC, PMMA, PTFE, soft plastics, neoprene or bituminous substrates.

DIRECTION

All surfaces must be clean, dry and dust free. All loose flaking surface coatings and old sealant should be removed by scraping, abrading or other suitable means prior to application. Glass and metal surfaces should be cleaned with appropriate solvent based cleaner, prior to applications to ensure optimum adhesion. Apply the product evenly to the surface. Smooth the product down after application using a spatula (or similar) wetted with water.

DOSAGE

Use the amount of which fits the treatment which fits the treatment. Store in a cool & dry area between 5°C and 40°C out of direct sunlight and protect from frost.

TECHNICAL SPECIFICATIONS

Colour	Black
Odour	Typical
Base	Acetoxy
Density	1,08 g/cm ³
Elongation at Break	400%
Skin formation @23°C	15 min
Operating temp.	-60°C to 330°C
Application temp.	5°C to 25°C

PACKAGING DETAILS

Art. No.	68781
Content	200 ml
Packaging	12x200 ml
Pallet	84 cartons
Languages	EN, DE, FR, ES, IT, RU

