MOTOR OIL
SAE 15W40 ECO

ОПИСАНИЕ ПРОДУКТА

ARDINA Motor Oil 15W40 Multigrade - это многоцелевое моторное масло, которое было произведено с использованием высококачественных базовых масел и высокотехнологичных присадок, но в сбалансированном виде, чтобы сохранить его экономичность. Это моторное масло разработано для использования в бензиновых и дизельных двигателях, с турбонагнетателями или без них, установленных в легковых и легких коммерческих автомобилях.

УРОВЕНЬ ПРОИЗВОДИТЕЛЬНОСТИ

- ACEA A3/B4
- API SL/CF
- MB 229.1
- VW 501.00/505.00

ТЕХНИЧЕСКИЕ ХАРАКТЕРИСТИКИ

Плотность кг/л @ 15°C	0,870
Вязкость @-35°C мПа.с	5290
Вязкость @40°C мм2/с	102,10
Вязкость @100°C мм2/с	13,70
Индекс вязкости	135
Температура вспышки COC	222°C
Точка застывания	-27°C
Общее количество основы	10,2 mgKOH/g
Зола, сульфатная	1,29%

ДЕТАЛИ УПАКОВКИ

Арт. No.	68516
	68517
	68518
Содержание	1L/4L/5L/200L
Поддон	N/A

ARDINA CAR CARE B.V. | Molenwerf 56 | 1911 DB Uitgeest | The Netherlands | sales@ardinacarcare.com

The content of this sheet is correct to the best of our knowledge. We do not accept responsibility for damage as a consequence of incompleteness or negligence and inaccuracies in this in- formation sheet. Recommendations or suggestions made in this sheet are made without guarantee of respresentations as to results. All terms of sale of the supplier are applied here.