

MOTOR OIL SAE 20W50 ST



ОПИСАНИЕ ПРОДУКТА

ARDINA Motor Oil SAE 20W50 ST - это многофункциональное моторное масло. Созданное на основе специально отобранных высококачественных базовых масел и в сочетании с подобранными высокотехнологичными присадками, это моторное масло подходит для использования в бензиновых/газолиновых и дизельных двигателях легковых автомобилей и фургонов с турбонагнетателями или без них.

УРОВЕНЬ ПРОИЗВОДИТЕЛЬНОСТИ

- ✓ ACEA A3/B4
- ✓ API SL/CF
- ✓ MB 229.1
- ✓ VW 501.01/505.00

ТЕХНИЧЕСКИЕ ХАРАКТЕРИСТИКИ

Плотность кг/л @15°C	0,893
Вязкость @-35°C мПа.с	9000
Вязкость @40°C мм2/с	164,00
Вязкость @100°C мм2/с	17,90
Индекс вязкости	120
Температура вспышки СОС	238°C
Точка застывания	-24°C
Общее количество основы	10,2 mgKOH/g
Зола, сульфатная	1,29%

ДЕТАЛИ УПАКОВКИ

Арт. No.	68524
	65736
Содержание	1L/4L/5L/200L
Поддон	N/A



ARDINA CAR CARE B.V. | Molenwerf 56 | 1911 DB Uitgeest | The Netherlands | sales@ardinacarcare.com

The content of this sheet is correct to the best of our knowledge. We do not accept responsibility for damage as a consequence of incompleteness or negligence and inaccuracies in this information sheet. Recommendations or suggestions made in this sheet are made without guarantee of representations as to results. All terms of sale of the supplier are applied here.