

PRODUCT DESCRIPTION

ARDINA ATF LV / VI is a high quality automatic transmission fluid with a high viscosity index and strong dispersion characteristics, which results in minimal sludge forming. It has a low pour point and excellent stability which protects against oxidation, wear and foam and is compatible with seals and non-ferro metals.

This ATF can be applied to automatic gear boxes (including hybrid), electric vehicles (EV) powertrains, power steering units, torque converters and other equipment, for which an ATF is required, which exceeds ATF Dexron III and II. Its special composition causes a longer lifetime of this liquid compared to older Dexron grades. This multi-vehicle ATF meets the hardware protection of the specified low viscosity fluids, like AW-2. This product cannot be used in DCT's and CVT's or when an oil with the Ford Type F/G specification is recommended.

PERFORMANCE LEVEL

- ✓ Aisin Warner JWS
3309(T-IV)/3324(WS)/AW-1/
AW-2
- ✓ Allison C3/C4, BMW
7045E/8072B/LA2634/ATF6/
Mini
- ✓ Cat TO-2, Chrysler Dodge
Mopar AS68RC/69RC (T-IV)
- ✓ Chrysler ATF+/-+2/+3, Fiat
Type IV/9.55550-AV5/AV-6
- ✓ Daihatsu ATF D-II/D-III SP
- ✓ Ford Mercon/LV/M2C138-
CJ/166-H/922-A1/924-
A/938-A
- ✓ GM Dexron VI/II/IID/IIE/IIIG/IIIH,
TASA
- ✓ Honda Acura DW-1/ATF-
Z1(except in CVT)
- ✓ Hyundai/Kia SP-II/SP-III/SP-IV/
SP-IV M/SP-IV RR
- ✓ Hyundai/Kia JWS
3314/9638,
- ✓ Isuzu ATF II/III/SP/WSI
- ✓ Jaguar ATF 3403 M115/
JLM 20238/20292
- ✓ JASO M315-2013 1A/1A-
LV/2A
- ✓ Mazda ATF DII/M-III/M-V/
FZ/A7/F-1/S-1/N-1/3317
- ✓ MB 236.1/2/3/236.5/236.7
/236.8/236.9/236.41
- ✓ Mitsubishi SK/SP-II/SP-III/
SP-IV/AW/J2/J3/ PA/MA1
- ✓ Nissan Matic C/D/J/K/P/
S/W,
- ✓ Porsche 3403-M115/T-IV
- ✓ Subaru ATF/5AT/HP
- ✓ Suzuki ATF
3309/3314/3317/2326/2384K,
- ✓ PSA B71 2340
- ✓ Toyota D-II/D-III/T-III/T-IV/WS,
- ✓ Tesla Model S/3/X
- ✓ VW G 052 025 / G 052 055 / G
052 162 / G 052 990
- ✓ VW G 053 001 / G 053 025 / G
055 005 / G 055 025
- ✓ VW G 055 162 / G 055 540 / G
060 162
- ✓ Voith 55.6335.xx (G607), Volvo
97335/97340/1161540
- ✓ ZF 5HP 8FL/19FL/24A/30/4HP20,
ML 05L/09/11A/B/21L

TECHNICAL SPECIFICATIONS

Density kg/L @ 15°C	0,845
Viscosity @ 40°C mm²/s	29,60
Viscosity @ 100°C mm²/s	5,90
Viscosity Index	149
Flash Point COC	212
Pour Point	-48°C
Colour	Red

PACKAGING DETAILS

Art. No.	68390 - 65745 - 65746 - 65749
Content	1L/4L/5L/200L
Pallet	N/A